

Specifications

| Model | | M130X |
|--|-----------------|---|
| Engine | | |
| Type (Make: Kubota) | | V6108 Common Rail, direct injection |
| No. of cylinders / Aspiration | | 4 / Turbocharger with intercooler |
| Rated speed | rpm | 2200 |
| Engine gross power | HP | 139.9 |
| Engine net power | HP | 130.0 |
| PTO power | HP | 113.0 |
| Total displacement | cm ³ | 6124 |
| Fuel tank capacity | ℓ | 190 |
| Air cleaner | | Dry, dual-element |
| Alternator | Amp | 80 |
| Transmission | | |
| No. of speeds | | 16 forward / 16 reverse (24 forward / 24 reverse w/ optional creep) |
| Max. speed | km/h | 40 |
| Main gear shift | | 8 speeds power shift (w/ auto) |
| Range gear shift | | 2 speeds, synchronised |
| Hydraulic shuttle | | Standard, column mounted lever |
| Main clutch type | | Hydraulic multi-plate wet disc |
| Brake type | | Hydraulic wet discs, 4-wheel braking |
| Trailer brake | | Standard |
| 4WD engagement system | | Electro-hydraulic w/ Bi-speed |
| Differential lock (Front / Rear) | | Hydraulic / Hydraulic |
| PTO | | |
| PTO type | | Live-independent PTO (electro-hydraulic) |
| Speed | rpm | 540 / 1000 |
| Hydraulics | | |
| Pump capacity (3-point hitch) | ℓ/min. | 77.0 |
| 3-point hitch (Category II) | | Quick-hitch lower link ends, telescopic stabilisers |
| Category | | II |
| Control system | | Position, draft control (lower link sensing) & mix control |
| Lift capacity at link end | kg | 5800 |
| No. of standard remote valves | | 2 standard (3rd, 4th & flow control valve optional) |
| Other features | | |
| Steering | | Hydrostatic power steering |
| Bonnet type | | Full-open, slanted |
| Deck type / Pedal type | | Full flat deck / Hanging pedals |
| Panel type | | Electronic |
| Standard tyre size (front / rear) | | |
| 420/70R24 / 520/70R38 | | |
| Dimensions & weight | | |
| Overall length | mm | 4400 |
| Overall height | mm | 2750 |
| Overall width (min.) | mm | 2175 |
| Wheelbase | mm | 2690 |
| Tread width | Front mm | 1660 – 1770 |
| | Rear mm | 1660 – 1755 |
| Turning radius (w/o brake) | m | 5.0 |
| Tractor weight (w/o ballast) | kg | 4424 |

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.
 For your safety, Kubota strongly recommends the use of a seat belt in almost all applications.
 For complete operational information, the operator's manual should be consulted.

©2010 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
 Phone Thame (01844) 214500 Fax (01844) 216685
 E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>